



## APPENDIX 1 -- PENDING CLAIMS

1. A spatial sound conference system comprising:  
a conference station comprising:  
right and left spatially disposed microphones connected to a communications channel for receiving right and left audio signals, wherein the differences between the right and left audio signals represent a head-related transfer function; and  
a remote station comprising:  
right and left spatially disposed loudspeakers connected to the communications channel.
2. A spatial sound conference system according to claim 1, further comprising:  
a compression unit connected to the right and left spatially disposed microphones for compressing the right and left audio signals; and  
a decompression unit connected to the right and left spatially disposed loudspeakers for decompressing the compressed right and left audio signals.
3. A spatial sound conference system according to claim 1, further comprising:  
a microphone positioned in the remote station and connected to the communications channel for receiving an audio signal; and  
a loudspeaker positioned in the conference station and connected through the communications channel to the microphone.
4. A spatial sound conference system according to claim 3, further comprising:  
a compression unit connected to the microphone positioned in the remote station for compressing the audio signal; and  
a decompression unit connected to the loudspeaker positioned in the conference station for decompressing the compressed audio signal.
5. A spatial sound conference system according to claim 1, wherein the right and left spatially disposed microphones are positioned on a dummy head.
6. A spatial sound conference system according to claim 5, further comprising:  
a microphone positioned in the remote station and connected to the communications channel for receiving an audio signal; and  
a loudspeaker positioned proximal to the dummy head and connected through the communications channel to the microphone.
7. A spatial sound conference system according to claim 5, further comprising:  
a microphone positioned in the remote station and connected to the communications channel for receiving an audio signal; and  
right and left spatially disposed loudspeakers positioned in the conference station and connected through the communications channel to the microphone.

8. A spatial sound conference system according to claim 5, further comprising:  
a head-tracking sensor in the remote station connected to the communications channel;  
and  
a position simulator attached to the dummy head and connected through the communications channel to the sensor.
9. A spatial sound conference system according to claim 1, further comprising:  
a video camera positioned in the conference station and connected to the communications channel for receiving a video image; and  
a display positioned in the remote station and connected through the communications channel to the video camera.
10. A spatial sound conference system according to claim 9, wherein the video camera is positioned near the location of eyes on a dummy head.
11. A spatial sound conference system according to claim 9, wherein the display is a head-mounted display.
12. A spatial sound conference system according to claim 1, wherein the right and left spatially disposed loudspeakers are a headset.
13. A method for conducting a spatial sound conference comprising the steps of:  
converting audio information into right and left audio signals at a conference station, wherein the conversion imparts a differential characteristic to the right and left audio signals, and the differential characteristic is represented by a head-related transfer function, and the right and left audio signals comprise spatialized audio;  
transmitting audio information representative of said spatialized audio from the conference station across a communications channel to a remote station; and  
playing the spatialized audio in the remote station.
14. A method for conducting a spatial sound conference according to claim 13, further comprising the steps of:  
compressing the right and left audio signals after the step of converting; and  
decompressing the compressed right and left audio signals after the step of transmitting.
15. A spatial sound conference system comprising:  
a transmitting station comprising:  
a microphone connected to a communications system for receiving an audio signal;  
a head-related transfer function unit connected to the communications system for imparting a head-related transfer function to the audio signal to produce a spatialized audio signal; and  
a receiving station comprising:  
right and left spatially disposed loudspeakers connected to the communication system for receiving the spatialized audio signal.

16. A spatial sound conference system according to claim 15, further comprising:  
a compression unit connected to the microphone for compressing the audio signal; and  
a decompression unit connected to the head-related transfer function unit for decompressing the compressed audio signal.
17. A spatial sound conference system according to claim 15, further comprising:  
a compression unit connected to the head-related transfer function unit for compressing the spatialized audio signal; and  
a decompression unit connected to the right and left spatially disposed loudspeakers for decompressing the compressed spatialized audio signal.
18. A spatial sound conference system according to claim 15, wherein the head-related transfer function unit is contained in a spatial sound conference bridge.
19. A method for conducting a spatial sound conference comprising the steps of:  
receiving an audio signal at a transmitting station;  
transmitting the audio signal from the transmitting station to a spatial sound conference bridge;  
imparting a head-related transfer function to the audio signal to create a spatialized audio signal;  
sending the spatialized audio signal from the spatial sound conference bridge to a receiving station; and  
playing the spatialized audio signal on spatially disposed loudspeakers at the receiving station.
20. A method for conducting a spatial sound conference according to claim 19, further comprising the steps of:  
compressing the audio signal after the step of receiving; and  
decompressing the compressed audio signal after the step of transmitting.
21. A method for conducting a spatial sound conference according to claim 19, further comprising the steps of:  
compressing the spatialized audio signal after the step of imparting; and  
decompressing the compressed spatialized audio signal after the step of sending.
22. A method for conducting a spatial sound conference comprising the steps of:  
receiving an audio signal at a transmitting station;  
transmitting the audio signal from the transmitting station to a receiving station;  
imparting a head-related transfer function to the audio signal to create spatialized audio signal;  
playing the spatialized audio signal on spatially disposed loudspeakers in the receiving station.

23. A method for conducting a spatial sound conference according to claim 22, further comprising the steps of:  
compressing the audio signal after the step of receiving; and  
decompressing the compressed audio signal after the step of transmitting.
24. A spatial sound conference bridge comprising:  
at least two input ports for receiving at least two audio signals and at least two audio signal output ports; and  
a head-related transfer function unit connected to at least one of said input ports for imparting a head-related transfer function to a corresponding audio signal to produce at least one spatialized audio signal; wherein  
a first output port is connected to the head-related transfer function unit for transmitting the spatialized audio signal.
25. A spatial sound conference bridge according to claim 24, further comprising:  
a decompression unit connected to at least one input port for decompressing at least one audio signal.
26. A spatial sound conference bridge according to claim 24, further comprising:  
a compression unit connected to at least one output port for compressing at least one spatialized audio signal.
27. A method for conducting a spatial sound conference comprising the steps of:  
receiving at least two monaural audio signals;  
generating at least two sets of spatialized audio signals from the at least two monaural audio signals using at least two head-related transfer functions;  
compiling at least one composite signal from the at least two sets of spatialized audio signals;  
transmitting at least one composite signal to a location; and  
playing at least one composite signal at the location.